



Fixture BELL M 32







OPTICS

"AS"





PRODUCT DESCRIPTION

Classic fixture adapted to be mounted on a boom (ř60 mm) at a height of 4-7 m. Aluminum body forms a sealed chamber (closed with a plate) with a sealed LED module (with the lens) mounted from the lamp-shade's side and a heat-sink and power supply unit - from the inside. The chamber is connected to the upper rosette, which - apart from its decorative function, also serves as a mounting bracket. Lamp-shade made of polycarbonate being resistant to UV radiation. Light source: LED panel with a system of lenses and reflector forming any required shape of light.

TECHNICAL SPECIFICATIONS

Voltage	230 V						
Source power / fixture	Recommended: Integrated 32 W/36 W						
Lifetime	70.000 h LB 80/20						
Optics	S AS ASP ASW						
Ambient Temperature	-30 ÷ +45						
Light color	4000 3000 *						
Ingress protection	IP65						
Protection class							
CE	Yes						
*choice MECHANICAL DATA							
Foundation	-						
Column/body material	Aluminium						
Lampshade	РММА						
Metal color	White 9003						
	Grey 7043						
	Graphite 7016						
	Black 9005						
	RAL*						
ON ORDER							
2700°K 300 mA 10	kV C Φ						

 \odot

DETAILED DESCRIPTION

"S"

INDEX	NAME	DIMENSIONS [cm]	LIGHT SOURCE			FIXTURE			WIND	WEIGHT
		L/B/H	W	Im	lm / W	W	lm	lm / W	m²	kg
195-1111-000078	BELL M 32	56/56/44	32	4900	154	36	3450	96	0,12	6

DIM

** on special order

5000°K | 1050 mA

Data for: Ra > 80, 4000K, 700mA. Source of light and integrated control gear, replacement only by the manufacturer's service.