





Fixture GAMMA LED 36 AS



OPTICS



„AS”

DETAILED DESCRIPTION

INDEX	NAZWA	WYMIARY [cm]	ŹRÓDŁO ŚWIATŁA			OPRAWA			WIATR	MASA
		L/B/H	W	lm	lm / W	W	lm	lm / W	m ²	kg
195-1111-000069	GAMMA LED 36 AS	56/56/65	32	4900	154	36	3550	98,5	0,10	4,5

Data for: Ra > 80, 4000K, 700mA. Source of light and integrated control gear, replacement only by the manufacturer's service.



PRODUCT DESCRIPTION

Modern fixture with a universal form, adapted to be mounted on a post at a height of 4-5 m. Body made of die-cast aluminum forms the grounds for a UV-resistant PMMA lamp-shade and its canopy, which is also a reflector. Energy-saving IP 65 LED module with a variety of light distributions. The whole is fastened together by an assembly frame. Lamp-shade made of transparent, UV-resistant PMMA or PC - on request.

TECHNICAL SPECIFICATIONS


Voltage	230 V
Source power / fixture	Recommended: Integrated 32 W/36 W
Lifetime	70.000 h LB 80/20
Optics	AS
Ambient temperature	-30 ÷ +45
Light color	4000 3000 *
Ingress Protection	IP65
Protection class	I II *
CE	Yes

* choice

MECHANICAL DATA

Foundation	-
Column/body material	Aluminium
Lampshade	PMMA
Metal color	<div style="display: flex; align-items: center;"> <div style="width: 20px; height: 20px; background-color: #f0f0f0; margin-right: 5px;"></div> White 9003 <div style="width: 20px; height: 20px; background-color: #808080; margin-right: 5px; margin-top: 5px;"></div> Grey 7043 <div style="width: 20px; height: 20px; background-color: #404040; margin-right: 5px; margin-top: 5px;"></div> Graphite 7016 <div style="width: 20px; height: 20px; background-color: #202020; margin-right: 5px; margin-top: 5px;"></div> Black 9005 <div style="margin-left: 10px; border: 1px solid black; padding: 2px;">RAL*</div> </div>

ON ORDER



** on special order