


Fixture GAMMA LED 26 COB





OPTICS



"S"

DETAILED DESCRIPTION



PRODUCT DESCRIPTION

Modern fixture with a universal form, adapted to be mounted on a post at a height of 4-5 m. Body made of die-cast aluminum forms the grounds for a UV-resistant PMMA lamp-shade and its canopy, which is also a reflector. Energy-saving IP 65 LED module with a variety of light distributions. The whole is fastened together by an assembly frame. Lamp-shade made of transparent, UV-resistant PMMA or PC - on request.

TECHNICAL SPECIFICATIONS

Voltage	230 V							
Source power / fixture	Recommended: Integrated 23,5 W/26 W							
Lifetime	70.000 h LB 80/20							
Optics	S							
Ambient temperature	-30 ÷ +45							
Light color	4000 3000 *							
Ingress Protection	IP65							
Protection class								
CE	Yes							
*choice MECHANICAL DATA Foundation	<u>-</u>							
Column/body material	Aluminium							
Lampshade	PMMA							
Metal color	White 9003							
	Grey 7043							
	Graphite 7016							
	Black 9005							
	RAL*							
DIM 2700°K 300 mA 5000°K 1050 mA 100	kv ⊖							

**on special order

INDEX	NAME	DIMENSIONS [cm]	SOURCE OF LIGHT		FIXTURE			WIND	WEIGHT	
		L/B/H	W	Im	lm / W	W	lm	lm / W	m²	kg
195-1111-000070	GAMMA LED 26 COB	56/56/65	23,5	4060	173	26	3300	126	0,10	4,5

Data for: Ra > 80, 4000K, 700mA. Source of light and integrated control gear, replacement only by the manufacturer's service.